

Price\* : 147.11 GBP



## Main

Range of product	OsiSense XU
Series name	Application
Specific application of photoelectric detector	Conditioning Packaging Control of objects in small and medium handling Detection of parts with remote amplifier
Sensor name	XUY
Sensor design	Fiber design
Number of channels	2
Emission	Red LED

## Complementary

Electronic sensor type	Photo-electric sensor
Material	Plastic
Enclosure material	ABS strong housing
Pulse frequency	3 kHz
Type of output signal	Discrete
Output type	Relay
Discrete output function	1 C/O
Electrical connection	Screw clamp terminals, 1.5 mm <sup>2</sup>
Supply circuit type	AC
[Us] rated supply voltage	115...230 V AC
Output voltage	250 V
Switching frequency	25 Hz
Power consumption in VA	4 VA
Maximum delay first up	20 ms
Maximum delay recovery	20 ms

## Environment

Product certifications	CE
Ambient air temperature for operation	0...60 °C

Ambient air temperature for storage	-20...80 °C
Immunity to ambient light	10000 lux incandescent bulb 10000 lux natural light

### Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

### Contractual warranty

Warranty	18 months
----------	-----------