

Price\* : 88.77 GBP



## Main

|                               |  |
|-------------------------------|--|
| Range of product              | OsiSense XU                                |
| Sensor name                   | XUY  |
| Sensor design                 | Fiber design                               |
| Sheath type                   | Standard                                   |
| [Sn] nominal sensing distance | 80 mm XUYAFV                               |
| End fitting type              | Pliable with nickel plated brass, M4 x 0.7 |

## Complementary

|                        |                          |
|------------------------|--------------------------|
| Electronic sensor type | Photo-electric sensor    |
| Optic fiber material   | 50 µ glass               |
| Sheath material        | PVC + thermo polyolefine |
| Detection system       | Diffuse                  |
| Optic fiber length     | 0.6 m                    |
| Minimum bending radius | 10 mm                    |
| Head mounting          | M4 x 0.7                 |
| Product weight         | 0.043 kg                 |

## Environment

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -25...60 °C |
|---------------------------------------|-------------|

## Offer Sustainability

|                            |   |
|----------------------------|---|
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|