



Price\* : 54.78 GBP



## Main

|                                    |                       |
|------------------------------------|-----------------------|
| Range of product                   | Harmony XVB Universal |
| Product or component type          | Indicator bank        |
| Beacon or indicator bank unit type | Illuminated unit      |
| Signalling type                    | Steady                |
| Mounting diameter                  | 70 mm                 |
| Component name                     | XVBC                  |
| Material                           | Polycarbonate         |
| Light source                       | Integral LED, orange  |
| Bulb type                          | Protected LED         |
| [Us] rated supply voltage          | 230 V AC              |

## Complementary

|                                        |                                                                  |
|----------------------------------------|------------------------------------------------------------------|
| Assembly style                         | Customer assembly, up to 5 units                                 |
| Connections - terminals                | Screw clamp terminals, <= 1 x 1.5 mm <sup>2</sup> with cable end |
| [Ui] rated insulation voltage          | 250 V conforming to IEC 60947-1                                  |
| Nominal voltage limit                  | 0.85...1.1 Un conforming to IEC 60947-5-1                        |
| Current consumption                    | < 17 mA AC                                                       |
| [Uimp] rated impulse withstand voltage | 4 kV IEC 60947-1                                                 |
| CAD overall width                      | 70 mm                                                            |
| CAD overall height                     | 63 mm                                                            |
| CAD overall depth                      | 70 mm                                                            |
| Product weight                         | 0.15 kg                                                          |

## Environment

|                        |                        |
|------------------------|------------------------|
| Pollution degree       | 2                      |
| Product certifications | CCC<br>CSA C22-2 No 14 |

|                                     |                                                                                                  |
|-------------------------------------|--------------------------------------------------------------------------------------------------|
|                                     | UL 508<br>GOST                                                                                   |
| Standards                           | EN/IEC 60947-5-1                                                                                 |
| Protective treatment                | TC                                                                                               |
| Ambient air temperature for storage | -40...70 °C                                                                                      |
| Electrical shock protection class   | Class I on support tube conforming to IEC 61140<br>Class II on base unit conforming to IEC 61140 |
| IP degree of protection             | IP65 on fixing base XVBZ0. conforming to IEC 60529<br>IP66 on base unit conforming to IEC 60529  |
| NEMA degree of protection           | NEMA 4X conforming to UL 508 (indoor)                                                            |

### Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                           |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | No need of specific recycling operations                                                                                    |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|