Product datasheet Characteristics

XVBC4M6 INDICATING BANK LENS 230VAC 10W +OPTIONS



Price*: 71.85 GBP



Main

Widin		
Range of product	Harmony XVB Universal	
Product or component type	Indicator bank	
Beacon or indicator bank unit type	Illuminated unit	
Signalling type	Flashing	
Mounting diameter	70 mm	
Component name	XVBC	
Material	Polycarbonate	
Light source	Bulb not included, blue	
Bulb type	Incandescent with BA 15d base Protected LED	
[Us] rated supply voltage	48230 V AC	

Complementary

Customer assembly, up to 5 units	
7 W	
Screw clamp terminals, <= 1 x 1.5 mm² with cable end	
250 V conforming to IEC 60947-1	
0.851.1 Un conforming to IEC 60947-5-1	
IEC 60947-1 4 kV	
1 Hz	
70 mm	
63 mm	
70 mm	
0.16 kg	
	7 W Screw clamp terminals, <= 1 x 1.5 mm² with cable end 250 V conforming to IEC 60947-1 0.851.1 Un conforming to IEC 60947-5-1 IEC 60947-1 4 kV 1 Hz 70 mm 63 mm 70 mm

Environment

Pollution degree	2	
Product certifications	CCC CSA C22-2 No 14 GOST UL 508	
Standards	EN/IEC 60947-5-1	
Protective treatment	TC	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-2550 °C: incandescent -2550 °C: LED	
Electrical shock protection class	Class I on support tube conforming to IEC 61140 Class II on base unit conforming to IEC 61140	
IP degree of protection	IP65 on fixing base XVBZ0. conforming to IEC 60529 IP66 on base unit conforming to IEC 60529	
NEMA degree of protection	NEMA 4X conforming to UL 508 (indoor)	

Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months	