



Price\* : 92.25 GBP



## Main

|                                    |                                                                          |
|------------------------------------|--------------------------------------------------------------------------|
| Range of product                   | Harmony XVB Universal                                                    |
| Product or component type          | Complete beacon                                                          |
| Beacon or indicator bank unit type | Base unit direct or tube fixing<br>Illuminated unit                      |
| Signalling type                    | Steady                                                                   |
| Mounting diameter                  | 70 mm                                                                    |
| Component name                     | XVBL                                                                     |
| Material                           | Glass reinforced polyamide: base unit<br>Polycarbonate: illuminated unit |
| Light source                       | Integral LED, yellow                                                     |
| Bulb type                          | Protected LED                                                            |
| [Us] rated supply voltage          | 24 V AC/DC                                                               |

## Complementary

|                                        |                                                                        |
|----------------------------------------|------------------------------------------------------------------------|
| Connections - terminals                | Screw clamp terminals, $\leq 1 \times 1.5 \text{ mm}^2$ with cable end |
| [Ui] rated insulation voltage          | 250 V conforming to IEC 60947-1                                        |
| Nominal voltage limit                  | 0.85...1.1 $U_n$ conforming to IEC 60947-5-1                           |
| Current consumption                    | $< 47 \text{ mA AC/DC}$                                                |
| [Uimp] rated impulse withstand voltage | 4 kV IEC 60947-1                                                       |
| CAD overall width                      | 70 mm                                                                  |
| CAD overall height                     | 139 mm                                                                 |
| CAD overall depth                      | 70 mm                                                                  |
| Terminals description ISO n°1          | (COM-1)PW<br>(GND)GROUND                                               |
| Product weight                         | 0.27 kg                                                                |

## Environment

|                                     |                                                                                                  |
|-------------------------------------|--------------------------------------------------------------------------------------------------|
| Pollution degree                    | 2                                                                                                |
| Product certifications              | GOST<br>UL 508<br>CSA C22-2 No 14<br>CCC                                                         |
| Standards                           | EN/IEC 60947-5-1                                                                                 |
| Protective treatment                | TC                                                                                               |
| Ambient air temperature for storage | -40...70 °C                                                                                      |
| Electrical shock protection class   | Class I on support tube conforming to IEC 61140<br>Class II on base unit conforming to IEC 61140 |
| IP degree of protection             | IP65 on fixing base XVBZ0. conforming to IEC 60529<br>IP66 on base unit conforming to IEC 60529  |
| NEMA degree of protection           | NEMA 4X conforming to UL 508 (indoor)                                                            |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                           |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | No need of specific recycling operations                                                                                    |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|