



Price\* : 126.92 GBP



### Main

|                                    |                                                                            |
|------------------------------------|----------------------------------------------------------------------------|
| Range of product                   | Harmony XVC4                                                               |
| Product or component type          | Complete pre-wired monolithic tower light                                  |
| Beacon or indicator bank unit type | 4 illuminated units                                                        |
| Sound signalling                   | Without                                                                    |
| Mounting diameter                  | 40 mm                                                                      |
| Component name                     | XVC                                                                        |
| Device short name                  | XVC                                                                        |
| Light source                       | LED steady red<br>LED steady orange<br>LED steady green<br>LED steady blue |
| Supply circuit type                | AC/DC                                                                      |

### Complementary

|                                        |                                                                                                                                                             |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                               | Polycarbonate: illuminated unit<br>ABS (acrylonitrile butadiene-styrene): base unit<br>PBT + ABS (UL94HB): top cover<br>SGP (chromium-plated): support tube |
| Mounting location                      | On support tube, 17 mm                                                                                                                                      |
| Product mounting                       | On support tube, 17 mm                                                                                                                                      |
| [Us] rated supply voltage              | 24 V                                                                                                                                                        |
| [Us] rated supply voltage              | 24 V                                                                                                                                                        |
| Cable cross section                    | 0.33 mm <sup>2</sup>                                                                                                                                        |
| AWG gauge                              | AWG 22                                                                                                                                                      |
| Cable length                           | 600 mm                                                                                                                                                      |
| Marking                                | CE                                                                                                                                                          |
| [Uimp] rated impulse withstand voltage | 0.8 kV                                                                                                                                                      |
| Current consumption                    | 100 mA                                                                                                                                                      |
| Flashing frequency                     | 1 Hz                                                                                                                                                        |

|                |          |
|----------------|----------|
| Product weight | 0.56 kg  |
| Height         | 508.5 mm |

## Environment

|                                       |                                                                                                                            |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Standards                             | EN/IEC 61000-6-3<br>EN/IEC 61000-6-2                                                                                       |
| Product certifications                | UL                                                                                                                         |
| Protective treatment                  | TC                                                                                                                         |
| Ambient air temperature for storage   | -35...70 °C                                                                                                                |
| Ambient air temperature for operation | -10...50 °C                                                                                                                |
| Electrical shock protection class     | Class I conforming to EN/IEC 61140                                                                                         |
| Overvoltage category                  | Class I conforming to EN/IEC 61140                                                                                         |
| IP degree of protection               | IP23 vertical surface installation conforming to EN/IEC 60529<br>IP54 flat surface installation conforming to EN/IEC 60529 |

## Offer Sustainability

|                            |                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                             |
| REACH free of SVHC         | Yes                                                                                               |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                               |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                            |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                     |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                           |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|