Product datasheet Characteristics

XVC4M45S 40mmTower ROGB PoleBuzzerFlash100-240VAC



Price*: 362.72 GBP



Main

Range of product	Harmony XVC4	
Product or component type	Complete pre-wired monolithic tower light	
Beacon or indicator bank unit type	4 illuminated units	
Sound signalling	Buzzer	
Mounting diameter	40 mm	
Component name	XVC	
Device short name	XVC	
Light source	LED steady or flashing red LED steady or flashing orange LED steady or flashing green LED steady or flashing blue	
Supply circuit type	AC	
Noise level	7085 dB (continuous or intermittent tone) at 1 m	

Complementary

Complementary		
Material	Polycarbonate: illuminated unit ABS (acrylonitrile butadiene-styrene): base unit PBT + ABS (UL94-V0): top cover SGP (chromium-plated): support tube	
Mounting location	On support tube, 17 mm	
Product mounting	On support tube, 17 mm	
[Us] rated supply voltage	100240 V	
[Us] rated supply voltage	100240 V	
Cable cross section	0.83 mm² 0.33 mm²	
AWG gauge	AWG 22 AWG 18	
Cable length	450 mm	
Marking	CE	

[Uimp] rated impulse withstand voltage	4 kV
Current consumption	95 mA
Fundamental frequency	2.23 kHz
Flashing frequency	1 Hz
Product weight	0.83 kg
Height	672.2 mm

Environment

Standards	EN/IEC 60947-5-1 EN/IEC 60947-1	
Product certifications	UL	
Protective treatment	TC	
Ambient air temperature for storage	-3570 °C	
Ambient air temperature for operation	-1050 °C	
Electrical shock protection class	Class I conforming to EN/IEC 61140	
Overvoltage category	Class I conforming to EN/IEC 61140	
IP degree of protection	ree of protection IP23 vertical surface installation conforming to EN/IEC 60529 IP54 flat surface installation conforming to EN/IEC 60529	

Offer Sustainability

Green Premium product	
Yes	
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Yes	
Yes	
China RoHS declaration	
Product Environmental Profile	
End of Life Information	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months	