# Product datasheet Characteristics

## XVC4M55S 40mmTower ROGBC PoleBuzzrFlash100-240VAC



Price\*: 398.96 GBP



#### Main

		4
Range of product	Harmony XVC4	
Product or component type	Complete pre-wired monolithic tower light	
Beacon or indicator bank unit type	5 illuminated units	, s
Sound signalling	Buzzer	, <u></u>
Mounting diameter	40 mm	
Component name	XVC	
Device short name	XVC	44 
Light source	LED steady or flashing red LED steady or flashing orange LED steady or flashing green LED steady or flashing blue LED steady or flashing clear	for determining to it.
Supply circuit type	AC	
Noise level	7085 dB (continuous or intermittent tone) at 1 m	

#### Complementary

Complementary		
Material	Polycarbonate: illuminated unit ABS (acrylonitrile butadiene-styrene): base unit PBT + ABS (UL94-V0): top cover SGP (chromium-plated): support tube	o de chi
Mounting location	On support tube, 17 mm	
Product mounting	On support tube, 17 mm	9
[Us] rated supply voltage	100240 V	**************************************
[Us] rated supply voltage	100240 V	
Cable cross section	0.33 mm² 0.83 mm²	- Andrews
AWG gauge	AWG 18 AWG 22	.9. F.
Cable length	450 mm	0 

Marking	CE
[Uimp] rated impulse withstand voltage	4 kV
Current consumption	110 mA
Fundamental frequency	2.23 kHz
Flashing frequency	1 Hz
Product weight	0.86 kg
Height	707.2 mm

### Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-5-1	
Product certifications	UL	
Protective treatment	TC	
Ambient air temperature for storage	-3570 °C	
Ambient air temperature for operation	-1050 °C	
Electrical shock protection class	Class I conforming to EN/IEC 61140	
Overvoltage category	Class I conforming to EN/IEC 61140	
IP degree of protection	IP23 vertical surface installation conforming to EN/IEC 60529 IP54 flat surface installation conforming to EN/IEC 60529	

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

#### Contractual warranty

•	
Warranty	18 months