



Price\* : 245.27 GBP



### Main

|                                    |                                                     |
|------------------------------------|-----------------------------------------------------|
| Range of product                   | Harmony XVC6                                        |
| Product or component type          | Complete pre-wired monolithic tower light           |
| Beacon or indicator bank unit type | 1 illuminated unit                                  |
| Sound signalling                   | Buzzer                                              |
| Mounting diameter                  | 60 mm                                               |
| Component name                     | XVC                                                 |
| Light source                       | LED steady or flashing red                          |
| [Us] rated supply voltage          | 100...240 V                                         |
| Supply circuit type                | AC                                                  |
| Noise level                        | 70...85 dB (continuous or intermittent tone) at 1 m |

### Complementary

|                                        |                                                                                                                       |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Material                               | Polycarbonate: illuminated unit<br>ABS (acrylonitrile butadiene-styrene): base unit<br>PBT + ABS (UL94-V0): top cover |
| Product mounting                       | On base                                                                                                               |
| Cable cross section                    | 0.33 mm <sup>2</sup><br>0.83 mm <sup>2</sup>                                                                          |
| AWG gauge                              | AWG 22<br>AWG 18                                                                                                      |
| Cable length                           | 750 mm<br>850 mm                                                                                                      |
| Marking                                | CE                                                                                                                    |
| [Uimp] rated impulse withstand voltage | 4 kV                                                                                                                  |
| Current consumption                    | 60 mA                                                                                                                 |
| Fundamental frequency                  | 2.23 kHz                                                                                                              |
| Flashing frequency                     | 1 Hz                                                                                                                  |
| Product weight                         | 0.49 kg                                                                                                               |
| Height                                 | 232 mm                                                                                                                |

## Environment

|                                       |                                                           |
|---------------------------------------|-----------------------------------------------------------|
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1                        |
| Product certifications                | UL                                                        |
| Protective treatment                  | TC                                                        |
| Ambient air temperature for storage   | -35...70 °C                                               |
| Ambient air temperature for operation | -10...50 °C                                               |
| Electrical shock protection class     | Class I conforming to EN/IEC 61140                        |
| IP degree of protection               | IP54 flat surface installation conforming to EN/IEC 60529 |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                           |
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|