

Main

Range of product	Harmony XVL
Product or component type	LED pilot light with black bezel
Component name	XVL
Mounting diameter	8 mm
Light source	Protruding LED
Light block colour	Green
Protection type	Without protection
Reverse polarity protection	Without
IP degree of protection	IP40 IP40 conforming to NF C 20-010

Complementary


Input current	≤ 30 mA DC
Connections - terminals	Tag for faston connectors Tag for soldering connectors
[Ui] rated insulation voltage	50 V conforming to IEC 60947-1
Bulb lifespan	≥ 100000 h
Terminals description ISO n°1	(X1-X2)PL
CAD overall width	10 mm
CAD overall height	10 mm
CAD overall depth	36 mm
Product weight	0.003 kg

Environment

Product certifications	CSA UL
Protective treatment	TC
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Class of protection against electric shock	Class III conforming to IEC 60536 Class III conforming to NF C 20-030
RoHS EUR status	Compliant
RoHS EUR conformity date	0730

LED Pilot Light

Dimensions




- (1) Tags for Faston connectors or soldered connections
e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

C		Ø	
mm	in.	mm	in.
32	1.26	12	0.47

LED Pilot Light

Panel Drilling



Ø min		G min		H min	
mm	in.	mm	in.	mm	in.
8.2	0.32	12.5	0.49	12.5	0.49