



Price\* : 128.42 GBP



## Main

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| Range of product          | Harmony XVS                                     |
| Product or component type | Siren                                           |
| Device short name         | XVS                                             |
| Colour                    | White                                           |
| Signalling type           | 2 tones siren                                   |
| [Us] rated supply voltage | 12 V AC/DC<br>24 V AC/DC                        |
| Noise level               | 106 dB (continuous or intermittent tone) at 1 m |

## Complementary

|                                        |                            |
|----------------------------------------|----------------------------|
| Material                               | PC: body                   |
| Product weight                         | 0.8 kg                     |
| Marking                                | CE                         |
| [Uimp] rated impulse withstand voltage | 0.8 kV                     |
| Current consumption                    | 300 mA at 24 V<br>500 mA   |
| Clamping connection capacity           | <= 1 x 1.5 mm <sup>2</sup> |
| Electrical connection                  | Cable: 6.5...8.5 mm        |
| Width                                  | 114 mm                     |
| Height                                 | 114 mm                     |
| Depth                                  | 153.2 mm                   |

## Environment

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1 |
| Protective treatment                  | TC                                 |
| Ambient air temperature for storage   | -35...70 °C                        |
| Ambient air temperature for operation | -30...50 °C                        |

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Electrical shock protection class | Class II conforming to EN/IEC 61140 |
| IP degree of protection           | IP53                                |

### Offer Sustainability

|                            |                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                             |
| REACH free of SVHC         | Yes                                                                                               |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                               |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                            |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                     |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                           |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Siren

Dimensions

