



Price\* : 223.01 GBP



### Main

|                           |                  |
|---------------------------|------------------|
| Range of product          | Harmony XVS      |
| Product or component type | Multisound siren |
| Device short name         | XVS              |

### Complementary

|                                        |                                                                                                                                                       |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Colour                                 | White                                                                                                                                                 |
| Material                               | ASA (Acrylonitrile Styrene Acrylate): front<br>ASA (Acrylonitrile Styrene Acrylate): back<br>PC (polycarbonate): back cover                           |
| Product weight                         | 1 kg                                                                                                                                                  |
| Marking                                | CE                                                                                                                                                    |
| Mounting support                       | Bracket                                                                                                                                               |
| Fixing mode                            | 3 holes Ø 9 mm                                                                                                                                        |
| [Uimp] rated impulse withstand voltage | 0.8 kV                                                                                                                                                |
| Current consumption                    | 350 mA at 24 V<br>250 mA at 12 V                                                                                                                      |
| Electrical connection                  | Cable: 6.5...8.5 mm, 0.33 mm <sup>2</sup> / AWG AWG 22 (signalling circuit)<br>Cable: 6.5...8.5 mm, 0.52 mm <sup>2</sup> / AWG AWG 20 (power circuit) |
| Width                                  | 140 mm                                                                                                                                                |
| Height                                 | 114 mm                                                                                                                                                |
| Depth                                  | 223 mm                                                                                                                                                |

### Environment

|                        |                                                        |
|------------------------|--------------------------------------------------------|
| Signalling type        | 43 tones siren                                         |
| Standards              | EN 61000-6-2<br>EN 55014-2<br>EN 55022<br>EN 61000-6-3 |
| Product certifications | UL                                                     |

|                                       |                                                     |
|---------------------------------------|-----------------------------------------------------|
| Protective treatment                  | TC                                                  |
| Ambient air temperature for storage   | -35...70 °C                                         |
| Ambient air temperature for operation | -10...50 °C                                         |
| Overvoltage category                  | Class II conforming to EN/IEC 61140                 |
| IP degree of protection               | IP53 conforming to EN/IEC 60529                     |
| [Us] rated supply voltage             | 12 V DC<br>24 V DC                                  |
| Noise level                           | 0...105 dB (continuous or intermittent tone) at 1 m |

### Offer Sustainability

|                            |                                                                                                   |
|----------------------------|---------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                             |
| REACH free of SVHC         | Yes                                                                                               |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                               |
| RoHS exemption information | <a href="#">Yes</a>                                                                               |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                            |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                     |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                           |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Siren

Dimensions

