


Price* : 153.09 GBP



Main

Range of product	Harmony XVS
Product or component type	Electronic alarm
Device short name	XVS

Complementary

Colour	Black
Material	PC (polycarbonate): terminal cover PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene): body
Product weight	0.4 kg
Marking	CE
Overvoltage category	Class II conforming to EN/IEC 61140
Mounting support	96 mm DIN rail
[Us] rated supply voltage	12...24 V DC
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	250 mA at 12 V 292 mA at 12 V 292 mA at 24 V 354 mA at 24 V
Clamping connection capacity	$\leq 1 \times 1.5 \text{ mm}^2$
Width	96 mm
Height	96 mm
Depth	58.1 mm

Environment

Discrete output type	PNP
Signalling type	16 tones alarm
Standards	EN/IEC 60947-5-1 EN/IEC 60947-1

Protective treatment	TC
Ambient air temperature for storage	-35...70 °C
Ambient air temperature for operation	-20...50 °C
IP degree of protection	Panel mounted: IP54 conforming to EN/IEC 60529
Noise level	0...96 dB (continuous or intermittent tone) at 1 m

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Electronic Alarm

Dimensions

