

XZSDE1113

connection base - 2 flat cables - AS-Interface
cabling system



Main

Range of product	AS-Interface cabling system
Accessory / separate part category	Connection accessories
Accessory / separate part type	Connection base
Accessory / separate part designation	Connection base for flat cable
Accessory / separate part destination	4-way interface AS-i V1
Range compatibility	Modicon TSX Micro automation platform
Cable profile	Flat
Connections - terminals	IDC

Complementary

Cable entry number	2
Product compatibility	AS-i bus Separate power supply
[Ie] rated operational current	≤ 2 A
[Ue] rated operational voltage	≤ 40 V
Product weight	0.07 kg

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

Offer Sustainability

RoHS (date code: YYWW)	Will be Compliant on 4Q2011
------------------------	-----------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.