



PRODUCT-DETAILS

YLS-7.9-100BC

CABLE TIE 100LB 4IN 316SS BLK COAT



General Information

Extended Product Type	YLS-7.9-100BC
Product ID	7TCG009420R0109
EAN	5414363072713
Catalog Description	CABLE TIE 100LB 4IN 316SS BLK COAT
Long Description	Ball-Lock 316 Stainless Steel Cable Tie, Black Polyester Coating, for Temperatures up to 150 Degrees Celsius for Indoor and Outdoor Applications, Length of 100mm (3.94 Inches), Width of 7.9mm (0.311 Inches), Thickness of 0.36mm (0.01 Inches), Tensile Strength Rating of 440 Newtons (100 Pounds)

Ordering

E-Number (Finland)	1370096
EAN	5414363072713

Dimensions

Product Net Width	0.311 in 7.9 mm
Product Net Depth / Length	3.94 in 100 mm
Product Net Weight	.006 lb 2.721 g

Container Information

Package Level 1 Units	100 piece
Package Level 1 Width	5.9 in 150 mm
Package Level 1 Height	0.6 in 15 mm
Package Level 1 Depth / Length	7.9 in 201 mm
Package Level 2 Units	2500 piece
Package Level 2 Width	5.9 in 150 mm
Package Level 2 Height	9.4 in 239 mm
Package Level 2 Depth / Length	11 in 279 mm
Package Level 3 Units	5000 piece
Package Level 3 Width	13 in 330 mm
Package Level 3 Height	10.8 in 274 mm
Package Level 3 Depth / Length	11.6 in 295 mm

Additional Information

Application	For Temperatures up to 150 Degrees Celsius for Indoor and Outdoor Applications
Brand / Label	Ty-Rap
Color	Black
Lock Type	Ball-Lock
Material	316 Stainless Steel
Number of Batteries	0
Product Name	STAINLESS STEEL CABLE TIE
Product Type	Stainless Steel
Special Functions	Black Polyester Coated
Tensile Strength	100 lb 440 N
Thickness	0.014 in 0.36 mm
UPC	786210749266

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	YLS-7.9-100BC
Instructions and Manuals	YLS-7.9-100BC

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5046 >> Stainless Steel Ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

