Product datasheet Characteristics

ZB4BZ1055 1-N/O AND 1-N/C CONTACT, WITH SPRING CLAMP AND



Price*: 9.98 GBP



Main

Range of product	Harmony XB4
Product or component type	Complete body/contact assembly
Device short name	ZB4
Fixing collar material	Zamak
Sale per indivisible quantity	1
Head type	Standard
Contacts type and composition	1 NO + 2 NC
Contact operation	Slow-break
Contact block type	Single
Device composition	Fixing collar Contact block

Complementary

CAD overall width	30 mm	
Product weight	0.064 kg	
Mechanical durability	10000000 cycles	
Contacts material	Silver alloy (Ag/Ni)	
[le] rated operational current	10 A, Q600 10 A, A600	-
Electrical durability	10000000 cycles, 10 A	
Device presentation	Basic sub-assemblies	

Environment

LITTIONICH		ž.
Protective treatment	TH	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-4070 °C	 g :
IP degree of protection	IP20 conforming to IEC 60529	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty 18 months
