Product datasheet Characteristics

ZB5AG0F022

selector switch operating head - fiat key



ı	VI	а	Ш	η

Range of product	Harmony XB5	
Product or component type	Head for key selector switch	
Device short name	ZB5	
Bezel material	Dark grey plastic	9
Mounting diameter	22 mm	
Sale per indivisible quantity	1	ţ
Shape of signaling unit head	Round	
Type of operator	stay put	
Operator profile	key switch	
Type of keylock	FIAT	<u></u>
Key withdrawal position	In any position	

Complementary

Complementary		<u> </u>
CAD overall width	29 mm	<u> </u>
CAD overall height	29 mm	
CAD overall depth	72 mm	
Product weight	0.057 kg	90
Mechanical durability	1000000 cycles	+ + + + + + + + + + + + + + + + + + +
Station name	XALD 15 cut-outs XALK 25 cut-outs	<u></u>
Electrical composition code	C4 for <6 contacts using single and double blocks in front mounting C5 for <5 contacts using single blocks in front mounting C6 for <5 contacts using single and double blocks in front mounting C7 for <4 contacts using single blocks in front mounting C8 for <4 contacts using single and double blocks in front mounting C11 for <3 contacts using single blocks in front mounting C3 for <6 contacts using single blocks in front mounting SF1 for <3 contacts using single blocks in front mounting SR1 for <3 contacts using single blocks in rear mounting	n is not intended as a substitiute

Environment

Livionitori		ŏ
Protective treatment	TH	This
Ambient air temperature for storage	-4070 °C	imer:
Ambient air temperature for operation	-4070 °C	iscla

Overvoltage category	Class II conforming to IEC 60536
IP degree of protection	IP66 conforming to IEC 60529 IP67 IP69 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m
IK degree of protection	IK06 conforming to IEC 50102
Standards	JIS C8201-5-1 CSA C22.2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 UL 508 EN/IEC 60947-5-4 JIS C8201-1
Product certifications	RINA UL listed GL CSA DNV BV LROS (Lloyds register of shipping)
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27

Contractual warranty

144	
Warrantv	18 months
vvarianty	18 months