Product datasheet Characteristics

ZB6EB3A

green light block with body/fixing collar with integral LED 12...24V

Price* : 6.69 GBP



Main

Wilder		
Range of product	Harmony XB6	
Product or component type	Complete body for pilot lights	
Device short name	ZB6	
Sale per indivisible quantity	5	
Connections - terminals	Pins for printed circuit board, connection size: 1 x 0.5 mm	
Light source	LED	
Bulb base	Integral LED	
Light block supply	Direct	
Light source colour	Green	
[Us] rated supply voltage	1224 V AC/DC	
·		

Complementary

Complementary	
Product weight	0.003 kg
Operating position	Any position
[Ui] rated insulation voltage	250 V (pollution degree 3) conforming to EN/IEC 60947-1
[Uimp] rated impulse withstand voltage	EN 60947-1 4 kV
Signalling type	Steady
Supply voltage limits	630 V AC/DC
Current consumption	15 mA
Surge withstand	1 kV in contact conforming to IEC 61000-4-5 2 kV in free air conforming to IEC 61000-4-5

Environment

Protective treatment	TC
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-2570 °C
Electrical shock protection class	Class II conforming to IEC 61140
Standards	JIS C 852 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14

	EN/IEC 60947-5-1 EN/IEC 60947-1
Product certifications	UL GOST CSA CCC
Vibration resistance	+/- 3 mm (f= 2500 Hz) conforming to IEC 60068-2-6 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27
Resistance to fast transients	2 kV conforming to IEC 61000-4-4
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3
Resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-2-6 8 kV in free air (in insulating parts) conforming to IEC 61000-2-6
Electromagnetic emission	Class B conforming to IEC 55011

Offer Sustainability

REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China RoHS Regulation	China RoHS declaration
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months