Product datasheet Characteristics

ZBV18G6

blue flashing light block for head Ø22 integral LED 120V screw clamp terminals





Main

IVIAIII		Š
Range of product	Harmony XB5 Harmony XB4	ָב נ
Product or component type	Light block	
Device short name	ZBV	———
Sale per indivisible quantity	5	
Connections - terminals	Screw clamp terminals, <= 2 x 1.5 mm ² with cable end conforming to EN 60947-1 Screw clamp terminals, >= 1 x 0.22 mm ² without cable end conforming to EN 60947-1	
Signalling type	Flashing	
Light source	Protected LED	
Bulb base	Integral LED	
Light block supply	Direct	
Light source colour	Blue	
[Us] rated supply voltage	110120 V AC at 50/60 Hz	0

Complementary

Product weight	0.017 kg	
Tightening torque	0.81.2 N.m conforming to EN 60947-1	
Shape of screw head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat Ø 4 mm screwdriver Slotted compatible with flat Ø 5.5 mm screwdriver	
Current consumption	14 mA	
Service life	100000 h at rated voltage and 25 °C	
Surge withstand	1 kV conforming to IEC 61000-4-5	
Mounting of block	Front mounting	
Electrical composition code M1 M2 M3 M4 M5		

M6 M10 MF1 P1 P2

PF1

Environment

Protective treatment	TH		
Ambient air temperature for storage	-4070 °C		
Ambient air temperature for operation	-4070 °C		
IP degree of protection	IP20 conforming to IEC 60529		
Standards	JIS C8201-5-1 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-1 UL 508 EN/IEC 60947-5-5 EN/IEC 60947-5-4 JIS C8201-1		
Product certifications	CSA UL listed		
Resistance to fast transients	2 kV conforming to IEC 61000-4-4		
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3		
Resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2		
Electromagnetic emission	Class B conforming to IEC 55011		

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collect never end up in rubbish bins	

Contractual warranty

Warranty	18 months	