



### Main

|                            |   |
|----------------------------|---|
| Range of product           | OsiSense XC                               |
| Series name                | Special format                            |
| Product or component type  | Limit switch head                         |
| Device short name          | ZC2J                                      |
| Head type                  | Rotary head                               |
| Product compatibility      | XC2J                                      |
| Associated lever           | ZC2JY715<br>ZC2JY615                      |
| Associated body            | ZC2JC15<br>ZC2JC25                        |
| Movement of operating head | Rotary                                    |
| Type of operator           | Stay put without operating lever stay put |
| Type of approach           | Lateral approach, 2 directions            |

### Complementary

|                  |                                   |
|------------------|-----------------------------------|
| Switch actuation | From left and right<br>CW and CCW |
| Positive opening | Without                           |
| Product weight   | 0.21 kg                           |
| Head material    | Metal                             |

### Environment

|                                       |                  |
|---------------------------------------|------------------|
| Ambient air temperature for operation | 10...120 °C      |
| Ambient air temperature for storage   | 10...120 °C      |
| Environmental characteristic          | High temperature |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| EU RoHS Directive        | Not applicable, out of EU RoHS legal scope    |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a> |
| Circularity Profile      | No need of specific recycling operations      |

Contractual warranty

---

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---