



### Main

|                            |  |
|----------------------------|--|
| Range of product           | OsiSense XC  |
| Series name                | Special format   |
| Product or component type  | Limit switch head  |
| Device short name          | ZC2J   |
| Head type                  | Plunger head   |
| Product compatibility      | XC2J   |
| Associated body            | ZC2JC46<br>ZC2JD46   |
| Movement of operating head | Linear   |
| Type of operator           | Side roller plunger spring return metal (with horizontal roller) |
| Type of approach           | Lateral approach, 2 directions                                   |

### Complementary

|                  |            |
|------------------|------------|
| Switch actuation | By 30° cam |
| Positive opening | Without    |
| Product weight   | 0.245 kg   |
| Head material    | Metal      |

### Environment

|                                       |                 |
|---------------------------------------|-----------------|
| Ambient air temperature for operation | -40...70 °C     |
| Ambient air temperature for storage   | -40...70 °C     |
| Environmental characteristic          | Low temperature |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| EU RoHS Directive        | Not applicable, out of EU RoHS legal scope    |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a> |
| Circularity Profile      | No need of specific recycling operations      |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|